

Carpet & Felt-Back Vinyl Adhesive

3000

○ PRIMARY

Roberts® 3000 is a carpet and sheet vinyl adhesive developed with a longer open time for the optimal positioning of felt-back vinyl flooring while it will also develop tack for the installation of most types of commercial carpets.

Features:

- Optimal open time for positioning felt-back sheet vinyl
- Exhibits good tack for most types of commercial carpets
- Enviro-Friendly – solvent-free and LEED® compliant; VOC <1g/L, SCAQMD Rule 1168
- Non-flammable. NFPA Class A and UBC Class 1 fire resistance ratings (ASTM E84)
- CRI Green Label Plus Certified – GPL#36471
- GoldGuard® antimicrobial product protection
- Traffic – moderate residential / light commercial

Uses:

For adhering carpet and felt-backed sheet vinyl.
 Carpet Backings – Polypropylene (ActionBac®), urethane foam (Enhancer™), polyurethane laminate (LifeSpan®), sponge-rubber, jute, and latex-foam.
 For backings not listed please contact our Technical Department at (706) 277-5294.

For interior installations only. Do not use this adhesive for pure vinyl or vinyl-backed products.

Substrates:

Concrete, APA rated plywood, oriented strand board (OSB) and terrazzo.

Surface Preparation:

Subfloors must be structurally sound, dry, smooth, flat, level and free of excess moisture/alkali and all substances (oil, wax, grease, paint, oil based sealers, etc.) that might interfere with the performance of the flooring or its installation.

Ensure the appropriate flatness/smoothness to prevent accelerated wear or “show through” (telegraphing).

All substrate cracks, holes, high spots and irregularities must be adequately repaired to ensure a smooth, finished appearance to prevent show through and accelerated wear. Patching compounds must be suitable for the use application, polymer-modified and applied according to the manufacturer’s instructions. Expansion or other moving joints must not be filled or covered with flooring. Refer to ASTM 710 Standard Practice for Preparing Concrete Floors.

Wood – Subflooring, such as APA underlayment grade plywood, hardwood, oriented strand board (lightly sanded), or other materials, must be flooring grade and installed to the manufacturer’s specifications with adequate ventilation and moisture protection. Ensure wood substrates have a minimum 18 in. crawl space with adequate ventilation and moisture barrier




protection. Cracks, chips and joints must be properly patched or repaired. Refer to ASTM F1482 Standard Practice for Installation and Preparation of Panel Type Underlayments to Receive Resilient Flooring. Refer to CRI Carpet Installation Standard available at www.carpet-rug.org.

General:

Ensure substrate, flooring material and adhesive are fully acclimated prior to installation at the same temperature and humidity level expected during normal use (between 65–95°F) with a relative humidity (RH) of no greater than 65%. Refer to flooring manufacturer’s specific recommendations and industry standards.

Materials and area temperature must be between 65–95°F with a maximum RH of 65% for 48 hours before and during installation as well as for 72 hours afterward. Large temperature or humidity increases or decreases can affect the flooring and performance of the installation. Ensure adequate ventilation during flooring installation.



FLOORING TYPE	TROWEL SIZE	ITEM #	COVERAGE
Carpet (polypropylene)	1/8 in. x 1/8 in. x 1/16 in. 	49737 / 10137-12	90–110 sq. ft. per gallon
Felt-Back Sheet Vinyl	1/16 in. x 1/16 in. x 3/32 in. 	49736 / 10121-12	160–180 sq. ft. per gallon
Felt-Back Sheet Vinyl	1/16 in. x 1/16 in. x 1/16 in. 	10-810 / 10-823 10125	170–190 sq. ft. per gallon

The trowel notches referenced are those typically recommended for the type of flooring being installed. They are normally the minimum size recommended. Surface conditions (roughness and porosity of substrate), type of flooring and backing will ultimately determine the required trowel notch size and coverage. Always check with the specific flooring manufacturer’s recommendations for their specific trowel requirements. Ensure 100% transfer of adhesive to the substrate and the flooring backing.

Physical Characteristics (70°F, RH 50%):

Product Type: SBR Latex
Open Time: Up to 60 minutes
Working Time: Up to 90 minutes
Moisture Vapor Emissions: 5 lbs. or less (ASTM F1869) / 80% or less (ASTM F2170)
pH Level: Must not exceed 9.0
Shelf Life: One year in unopened container
Storage: Protect from freezing

Application and Installation:

Spread adhesive uniformly. Allow up to 45 minutes of open time before you place your flooring into the adhesive. Adhesive ridges should be of sufficient height to achieve full coverage of the substrate and the deepest recesses in the back of the flooring material.

Within the 65 minute working time, place flooring into the adhesive while the adhesive is still fresh and transfers readily to the flooring backing. The amount of open time and time in which you have time to place the flooring will vary with temperature and humidity. The higher the temperature and the lower the humidity the faster the adhesive will set.

Lift a corner periodically to see if the adhesive is transferring 100% to the back of the flooring. If the adhesive is not transferring to the backing of the underlayment remove adhesive and reapply.

After Installation – Restrict foot traffic and moving of heavy objects for 24 to 48 hours to allow adhesive to cure properly. Premature traffic can cause installation failure.

Clean Up:

Fresh adhesive – warm soapy water. *Dried adhesive* – use mineral spirits sparingly with a clean, white cotton cloth. **DO NOT POUR CLEANER DIRECTLY ONTO FLOORING.**

Limited Warranty:

1-Year Direct Bond. Roberts warrants that this product will be free from manufacturing defects for 12 months from the date of purchase, when applied in accordance with Roberts' instructions and industry standards. Roberts' sole liability is to either supply new product or refund the original purchase price. **This limited warranty excludes all other express warranties including the warranties of merchantability for a particular use or purpose.**

Any implied warranties arising by operation of law are limited to one year. Roberts will not be liable for any incidental or consequential damages. Visit www.robertsconsolidated.com for full warranty details.



Refer to material safety data sheet, www.robertsconsolidated.com, industry standards and manufacturer's guidelines prior to installation for additional information.

For technical assistance please contact our Technical Department at (706) 277-5294.

Available Sizes:

SIZE	PRODUCT #	UPC
5 Gallon	3000-5	075378300052
4 Gallon	3000-4	075378300045
1 Gallon	3000-1	075378300014
1 Quart	3000-0	075378300007

made in
USA

WARNING: EXISTING FLOORING AND ADHESIVES MAY CONTAIN ASBESTOS. Unless you have confirmation that the existing flooring system is not asbestos containing, do not sand, dry sweep, dry scrape, abrade, drill, saw, bead blast, mechanically chip or pulverize existing flooring or adhesive without taking all appropriate precautions. Refer to local, state and federal guidelines for treatment and removal of these products. You may also refer to the Resilient Floor Covering Institute's "Recommended Work Practices for Removal of Resilient Floor Coverings."

EXISTING PAINT MAY CONTAIN LEAD. Unless you have confirmation that the existing paint is not lead containing, do not sand, dry sweep, dry scrape, abrade, drill, saw, bead blast, mechanically chip or pulverize existing paint without taking all appropriate precautions. Refer to local, state and federal guidelines for treatment and removal of lead containing paint. You may also refer to www.epa.gov/lead