



7500

VINYL SEAM SEALER FOR SHEET FLOORING



Powered by Microban® for superior mold and mildew protection.

1. DESCRIPTION

ROBERTS® 7500 VINYL SEAM SEALER is a strong adhesive designed to seal seams in sheet flooring. With its easy application and clean-up, this durable bonding seam sealer is used with fiberglass-backed, felt-backed, heterogeneous and linoleum sheets goods

Features and Benefits

- Simple one-part application with easy clean up
- Creates strong, durable bond that can be walked on within two hours
- Fiberglass-back, felt-back, heterogeneous and linoleum sheet goods
- Coverage up to 144 linear feet / per 8 oz
- Powered by Microban® for superior mold and mildew protection

Approved Flooring Types

Fiberglass-backed sheet vinyl

Felt-backed sheet vinyl

Linoleum

For floorings and backings not listed, contact Technical Services at (706) 277-5294 (U.S.A) and (905) 791-4444 (CA).

2. TECHNICAL DATA

Product Type:	Polymer-Synthetic Resin
Color:	White
Odor:	Very mild, non-offensive
Open Time:	Up to 30 minutes
Working Time:	Up to 15 minutes <i>Setup time will vary slightly with temperature and porosity of substrate</i>
Curing Time:	2-6 hours. Do not roll heavy furniture or appliance over the newly created seam for 24 hours.
Traffic:	Residential: 24 hours Commercial: 24 hours Rolling Loads: N/A
pH:	5.5
Shelf Life:	1 year from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning
Storage:	Protect from freezing
VOC:	<1 g/mL



3. INSTRUCTIONS

Limitations

- For interior installations only
- Not for use in healthcare installs where an aseptic environment is necessary
- Not for use on degraded / ripped / rolled seams, or for use as gap filler

Installation

Overlap and double cut the seam using a scrap piece of flooring, under the cut location. Roll the flooring back. Finish gluing the seam area. Fold one side into the adhesive or on tape. Apply a 1/8" bead along the seam edge and tuck edge into place. Wipe seam with a dry, clean white cloth. Roll seam with a hand roller. Repeat as needed. Clean the seam again with the same process.

Clean-up

Fresh adhesive – warm, soapy water on a clean cloth.

Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth. DO NOT POUR DIRECTLY ONTO FLOORING.

4. AVAILABILITY



8 Oz Plastic Bottle	7500-8	075378750086
---------------------	--------	--------------



236 mL Plastic Bottle	7500RB250	075378750086
-----------------------	-----------	--------------



5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications. Visit robertsconsolidated.com, robertsconsolidated.com/ca or call (866) 435-8665 for full warranty details.

6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 U.S.A. / (905) 791-4444 Canada.



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company.

H1924 12281



Roberts Consolidated Industries, Inc.
 300 Cross Plains Blvd, Dalton, GA 30721
 Customer Service: (866) 435-8665
 Technical Support: (706) 277-5294
robertsconsolidated.com



Roberts Company Canada, Ltd.
 34 Hansen Road, Brampton, ON L6W 3H4
 Customer Service: (866) 435-8665
 Technical Support: (905) 791-4444
robertsconsolidated.com/ca

