

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** 8200 QUICKBOND All Purpose Spray Adhesive  
**Product Code:** 8200-12

**Manufacturer/ Supplier:** Roberts Consolidated Industries, Inc.  
**Address:** 300 Cross Plains Blvd.  
Dalton, GA 30721

**Emergency Phone:** (800) 424-9300 (24-hour Response / CHEMTREC)  
**Product Information:** (706) 277-5294  
**Recommended Use:** Adhesive

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Liquefied gas; Eye Irrit. 2; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1

### Label elements

Hazard Symbol



Signal word(s)

**DANGER**

Hazard Statement(s)

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes serious eye irritation.  
Causes skin irritation.  
May cause drowsiness or dizziness.  
May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Avoid breathing spray.  
Use only outdoors or in a well-ventilated area.  
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.  
Wash hands and exposed skin after use.  
Wear protective eyewear (goggles, face shield, or safety glasses).  
Wear protective gloves.  
Avoid release to the environment.  
Keep out of reach of children.  
Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

**Other hazards**

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Acetone	15-20	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Heptane, branched, cyclic, and linear	20-25	426260-76-6	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 2; H401 Aquatic Chronic 3; H412
Methyl Acetate	15-20	79-20-9	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Propane	15-25	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Styrene-butadiene-divinyl benzene polymer	5-10	26471-45-4	Not classified as dangerous for supply/use.
Hydrocarbon resin	10-20	Proprietary	Not classified as hazardous for supply/use
Rosin ester	1 - 5	Proprietary	Not classified as hazardous for supply/use

**Additional Information** - None

\* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

### SECTION 4: FIRST AID MEASURES



#### Description of first aid measures

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact

Wash affected skin with soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

Do not give anything by mouth to an unconscious person. Seek medical treatment. Do NOT induce vomiting.

**Most important symptoms and effects, both acute and delayed**

May cause drowsiness and dizziness. Aspiration of droplets may cause pulmonary oedema.

**Indication of any immediate medical attention and special treatment needed**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

### SECTION 5: FIRE-FIGHTING MEASURES

#### Extinguishing Media

-Suitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.

-Unsuitable Extinguishing Media

Do not use water jet.

**Special hazards arising from the substance or mixture**

Highly flammable vapor (flash point below 23°C).

**Advice for fire-fighters**

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing vapors.

**Environmental precautions**

Prevent liquid entering sewers, basements and work pits.

**Methods and material for containment and cleaning up**

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

**Reference to other sections**

None

**Additional Information**

None

## SECTION 7: HANDLING AND STORAGE

**Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.

**Conditions for safe storage, including any incompatibilities**

-Storage temperature

Store locked up. Keep in a cool, well ventilated place. Protect from sunlight. Store at temperatures not exceeding 50 °C / 122 °F. Keep container tightly closed.

-Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

**Specific end use(s)**

Adhesive Product

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits**

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Heptane, branched, cyclic, and linear	426260-76-6	500 ppm*	1500 mg/m <sup>3</sup>	----	----	*n-heptane
Acetone	64-64-1	----		----	----	
Propane	74-98-6	1000 ppm	Aspyx.#	----	----	#

\*Assure minimum oxygen content of work atmosphere.

**Recommended monitoring method**

NIOSH 1550 (Naphthas); NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1300 (Ketones I).

**Exposure controls**

**Appropriate engineering controls**

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

**Personal protection equipment**

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Butyl rubber)

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

**Environmental Exposure Controls**

None known

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Aerosol spray
Color.	Colorless
Odor	Not available
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation Rate	Not available
Flammability (solid, gas)	Highly flammable
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
VOC Content:	40%
Vapor pressure (Pascal)	ca. $95 \times 10^4$ (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	450 (Propane)
Decomposition Temperature (°C)	Not available
Kinematic Viscosity @38.7°C	0.83 mm <sup>2</sup> /sec (Heptane, branched,cyclic, and linear)
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
<b>Other information</b>	Not available

## SECTION 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	Stable under normal conditions.
<b>Chemical stability</b>	Stable.
<b>Possibility of hazardous reactions</b>	None anticipated.
<b>Conditions to avoid</b>	Avoid contact with heat and ignition sources.

**Incompatible materials**

Strong oxidizing agents. Reducing agents. Acids. Bases. Chlorinated compounds. Aldehydes. Acetone may form explosive mixtures in contact with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide and thioglycol.

**Hazardous decomposition product(s)**

Forms carbon oxides under fire conditions.

<b>SECTION 11: TOXICOLOGICAL INFORMATION</b>
--

**Exposure routes:** Inhalation, Skin Contact, Eye Contact

**Information on toxicological effects**

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

**Acute toxicity** (calculated / estimated)

Oral: LD50 >5 g/kg-bw  
 Dermal: LD50 >2 g/kg-bw  
 Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat  
 May cause drowsiness or dizziness.  
 May be fatal if swallowed and enters airways.

**Irritation/Corrosivity**

Causes skin irritation. Repeated exposure may cause skin dryness or cracking.  
 May cause eye irritation.

**Sensitization**

It is not a skin sensitizer.

**Repeated dose toxicity**

NOAEC: 12350 mg/m<sup>3</sup> (2 yr, inhal., rat, Systemic effects)  
 LOAEC: 1650 mg/m<sup>3</sup> (2 hr, inhal., rat, CNS effects)  
 May cause drowsiness or dizziness.

**Carcinogenicity**

No data. It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

**Mutagenicity**

There is no evidence of mutagenic potential.

**Reproductive toxicity**

No information available

Acetone (CAS No. 67-64-1):

**Acute toxicity**

Oral LD50 = 5800 mg/kg (rat)  
 Dermal LD50 >15800 mg/kg (rabbit)  
 Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness.

**Irritation / Corrosivity**

Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.

**Sensitisation**

It is not a skin sensitiser.

**Repeated dose toxicity**

Oral NOAEL = 900 mg/kg/day (rat) (90-days)  
 Inhalation NOAEL ≥ 19,000 ppm (rat)

**Carcinogenicity**

It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

**Mutagenicity**

Negative

**Toxicity for reproduction**

Negative

**Other information**

None known.

<b>SECTION 12: ECOLOGICAL INFORMATION</b>
---

**Ecotoxicity**

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term	LL50 (96 hour): >13.4 mg/L ( <i>Oncorhynchus mykiss</i> ) EL50 (48 hour): 3 mg/l ( <i>Daphnia magna</i> , mobility) EC50 (96 hour): 13 mg/l ( <i>Pseudokirchnerella subcapitata</i> )
Long Term	NOELR (28 days) 1.5 mg/l ( <i>Fish</i> ) QSAR LOEC (21 days): 0.32 mg/l ( <i>Daphnia magna</i> ) NOEL (96 hour) 6.3 mg/l ( <i>Algae</i> )
<b>Acetone (CAS No. 67-64-1):</b>	
Short term	LC50 (96 hour): 5,540 mg/l (Rainbow Trout ( <i>Oncorhynchus mykiss</i> )) LC50 (96 hour): 8,300 mg/l (Bluegill Sunfish ( <i>Lepomis macrochirus</i> )) LC50 (48 hour(s)): 12,600 – 12,700 mg/l ( <i>Daphnia magna</i> ) EC50 (14 d): 3,020 mg/l (Algae ( <i>Chlorella pyrenoidosa</i> )) EC50 (15 min): 14,500 mg/l (Bacteria ( <i>Photobacterium phosphoreum</i> ))
Long Term	Not available.
Persistence and degradability	Readily biodegradable. (anaerobic) 78%; OECD 301 D
Bioaccumulative potential	Not available.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not available.
Other adverse effects	None known.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste treatment methods** Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

**SECTION 14: TRANSPORT INFORMATION**

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

**SECTION 15: REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture:**

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Acetone	67-64-1	23	5000

SARA 311/312 - Hazard Categories: See SECTION 2: HAZARDS IDENTIFICATION

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
None	---	---

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
---------------	---------	--------------	--------------

None	----	----	----
------	------	------	------

**California Proposition 65 List:**

Chemical Name	CAS No.	Type of Toxicity
NONE	-----	-----

**SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: 1-16

**Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:**

**Hazard Statement(s)**

- H220: Extremely flammable gas.
- H222: Extremely flammable aerosol.
- H225: Highly flammable liquid and vapor.
- H229: Pressurised container: May burst if heated.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H401: Toxic to aquatic life.
- H412: Harmful to aquatic life with long lasting effects.

**Training advice:** None.

**Prepared by:** Roberts Consolidated Product Safety & Regulatory Compliance Group, (706) 277-5294

The information herein is given in good faith, but no warranty expressed or implied is made. Roberts Consolidated urges users of this product to evaluate its suitability and compliance with local regulations as Roberts Consolidated cannot foresee the final use of the product, nor the final location of usage.

**Date of Issue:** 05/06/2024