



8200

QUICKBOND ALL-PURPOSE SPRAY ADHESIVE

1. DESCRIPTION

ROBERTS® 8200 QUICK BOND® All-Purpose Spray Adhesive is a water-resistant, fast-tacking aerosol adhesive with excellent repositioning and the versatility to be used on a wide array of substrates. ROBERTS 8200 is formulated to bond carpet, carpet pad, drywall, masonry, wood, fiberglass to metal, blocks (polyurethane insulation), polyethylene film paper, and a variety of other substrates including cardboard, fabric, leather, foil, and rubber.

Features and Benefits

- Fast tack, fast-grab web spray
- Low soak-in with high-bond strength
- Permanent or repositionable bond
- Does not contain chlorofluorocarbons (CFC's), ozone depleting chemicals, or methylene chloride
- Coverage up to 100 ft² / 12 oz can
- Commercial and residential use

Approved Usage Types

Carpet / carpet repair

Carpet pad

Drywall / masonry / wood

Fiberglass to metal

Blocks (polyurethane insulation)

Polyethylene film

Sanding discs / bead boards

Approved Substrates

Concrete

APA-rated plywood

Existing VCT (free of wax/finish)

Primed gypcrete (refer to ASTM F2419)

Terrazzo

For floorings and backings not listed, contact Technical Services at (706) 277-5294 (U.S.A) and (905) 791-4444 (CA).

LIMITATIONS

- Not recommended for unsupported vinyl fabric. Certain plastic and elastomeric substrates can exhibit bond failure due to plasticizer migration. Combinations of high temperature and humidity can promote bond failure. For nonmetallic substrates, testing of production parts in typical operating environments for compatibility and performance is recommended.
- Use only outdoors or in a well-ventilated area.



STORAGE & HANDLING

- Store indoors only. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.
- **EXTREMELY FLAMMABLE.** Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 C / 122F. Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

2. TECHNICAL DATA

Product Type:	Web-Spray Adhesive
Color:	White
Odor:	Mild
Open Time:	Up to 2 minutes
Working Time:	Up to 15 minutes
Cure Time	Up to 12 hours
Shelf Life:	1 year in unopened container
Storage:	Protect from freezing
VOC:	40%

3. INSTRUCTIONS

Preparation

Surface must be structurally sound, dry and free from dirt, dust, old adhesive, wax, oil or grease.

Application

Hold can 8 to 12 inches from surface to be sprayed, and keep can moving to achieve an even coat of adhesive. For a permanent bond, spray both surfaces, allow adhesive to dry to tack and bond. For a temporary or repositionable hold, spray one surface only.

NOTE: Use as directed. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Curing

High temperature and low humidity will cause the adhesive to cure faster.

Clean-up

Dried adhesive – rub off or use mineral spirits sparingly with a clean, white cotton cloth. **DO NOT POUR CLEANER DIRECTLY ONTO FLOORING.**

4. AVAILABILITY



12 oz Spray Can	8200-12	075378820017
-----------------	---------	--------------



12 oz Spray Can	8200RB355	075378820017
-----------------	-----------	--------------

Not labeled for sale in retail stores in Canada



5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications. **Visit robertsconsolidated.com, robertsconsolidated.com/ca or call (866) 435-8665 for full warranty details.**

6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 U.S.A. / (905) 791-4444 Canada.

⚠️ WARNING: Cancer, Birth Defects and Reproductive Harm - www.P65Warnings.ca.gov.



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council®

Y0924-12180



Roberts Consolidated Industries, Inc.
300 Cross Plains Blvd, Dalton, GA 30721
Customer Service: (866) 435-8665
Technical Support: (706) 277-5294
robertsconsolidated.com



Roberts Company Canada, Ltd.
34 Hansen Road, Brampton, ON L6W 3H4
Customer Service: (866) 435-8665
Technical Support: (905) 791-4444
robertsconsolidated.com/ca

