



3030

MULTIPURPOSE Carpet and Sheet Vinyl Adhesive



Powered by Microban® for superior mold and mildew protection.

1. DESCRIPTION

ROBERTS® 3030 is a multipurpose adhesive designed for the installation of carpet and sheet vinyl flooring. It is a good tacking adhesive which offers great flexibility in open time – not too fast, not too slow for mid-sized jobs.

Features and Benefits

- Medium tack development
- Great adjustability time
- Coverage up to 180 ft²/gal
- Heavy residential / moderate commercial use
- Powered by Microban® for superior mold and mildew protection

Approved Flooring Types

Commercial carpet

Residential carpet

Felt-backed sheet vinyl

Approved Substrates

Concrete

Terrazzo (properly prepared)

CANPLY/APA-rated plywood

Underlayment-rated plywood

OSB (oriented strand board) lightly sanded

For floorings and backings not listed, contact Technical Services at (905) 791-4444 (CA).

Recommended Trowel and Coverage Rate*

1/8" x 1/8" x 1/16" (3 mm x 3 mm x 1.5 mm) V Notch

Flooring (porous substrate): Carpet Backings:
(Woven & Polypropylene)
Coverage: 90-110 ft²/per gallon (8.3-10.2 m²/per 3.78 L)

1/16" x 1/16" x 3/32" (1.5 mm x 1.5 mm x 2.3 mm) U Notch

Flooring (porous substrate): Felt-Backed Sheet Vinyl
Coverage: 160-180 ft²/per gallon (14.8-16.7 m²/per 3.78 L)

1/16" x 1/16" x 1/16" (1.5 mm x 1.5 mm x 1.5 mm) SQ Notch

Flooring (porous substrate): Carpet Backings:
(Non-Woven, Closed Cell & Enhancer)
Coverage: 65-75 ft²/per gallon (6-6.9 m²/per 3.78 L)

For natural fiber carpeting see additional table on pg 2.

** NOTE: The trowel notches referenced are those typically recommended for the type of flooring being installed, and are referenced as a guide. Coverage rates will vary depending on trowel type, substrate and installation conditions. Consult flooring manufacturer for their specific trowel recommendations.*



SHELF LIFE
2 YEARS



LIFETIME
WARRANTY*

*Based on installation by an industry certified installer

Recommended Trowels for Installation of Natural Fiber Carpeting*

| Method | Carpet Backing | Trowel Dimensions | Notch |
|------------------|----------------------|--------------------|-------|
| Direct Glue Down | Smooth or Rough Back | 1/8" x 1/8" x 1/8" | U |

| Method | Carpet Backing | Trowel Dimensions | Notch |
|------------------|--|-----------------------|-------|
| Double Glue Down | Between Floor & Cushion | 1/16" x 1/16" x 1/16" | SQ |
| | Between Cushion & Carpet (Smooth Back) | 1/8" x 1/16" x 1/8" | U |
| | Between Cushion & Carpet (Rough Back) | 1/8" x 3/16" x 1/8" | U |

*Per industry association guidelines

2. TECHNICAL DATA

| | |
|----------------------|--|
| Product Type: | SBR Latex |
| Color: | Tan |
| Odor: | Mild, sweet |
| Open Time: | Up to 30 minutes |
| Working Time: | Up to 90 minutes |
| | Setup time will vary slightly with temperature and porosity of substrate |
| Curing Time: | 24 hours |
| Traffic: | Residential: 12 hours Commercial: 24 hours Rolling Loads: N/A |
| MVER: | 5 lbs or less (ASTM F1869) / 80% RH or less (ASTM F2170) |
| pH: | Must not exceed 10.0 |
| Shelf Life: | 2 years from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning |
| Storage: | Protect from freezing |
| VOC: | <1 g/L |

3. INSTRUCTIONS

Limitations

- For interior installations only
- Do not use this adhesive for pure vinyl or vinyl-backed products

Preparation

Subfloors must be structurally sound, dry, smooth, at ($\leq 3/16"$ within 10'), level and free of excess moisture/alkali and all contaminants (oil, debris, paint, sealers, adhesive residue, etc.) that may inhibit the bond of the adhesive or the performance of the flooring and its installation. All substrate cracks, chips, holes, joints, high spots and irregularities must be adequately repaired. Patching compounds must be suitable for the use application, cement-based and polymer-modified, and applied according to the manufacturer's instructions.

Installation

Materials and area temperature must be between 65–95°F with a maximum RH of 65% for 48 hours, before and during installation, as well as for 72 hours afterward. Large temperature or humidity increases or decreases can affect the flooring and performance of the installation. Lift a corner periodically to ensure 100% coverage of adhesive to the floor backing and the substrate to ensure a void-free bond.

Spread adhesive uniformly. Adhesive ridges should be of sufficient height to achieve full coverage of the substrate and the back of the flooring.

Place flooring into the adhesive while the adhesive is still fresh. The amount of time in which you have to place the flooring will vary with temperature and humidity.

Clean-up

Fresh adhesive – warm, soapy water on a clean cloth.

Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth. DO NOT POUR DIRECTLY ONTO FLOORING.

4. AVAILABILITY

CANADA

| | | |
|---------------------|-----------|--------------|
| 18.9 L Plastic Pail | 3030RB020 | 075378303053 |
| 3.78 L Plastic Pail | 3030RB004 | 075378303015 |
| 946 mL Plastic Pail | 3030RB001 | 075378303008 |



5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications. **Lifetime Warranty applies only for installations performed by industry certified professional installers.**

Visit robertsconsolidated.com/ca or call (866) 435-8665 for full warranty details.

6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (905) 791-4444 Canada.



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company.

A2624 12309



Roberts Company Canada, Ltd.
34 Hansen Road, Brampton, ON L6W 3H4
Customer Service: (866) 435-8665
Technical Support: (905) 791-4444
robertsconsolidated.com/ca

a quality brand of
QEP