

# 7051

## WALL BASE ADHESIVE



Powered by Microban® for superior mold and mildew protection.

### 1. DESCRIPTION

**ROBERTS® 7051** is a superior-performing wall base adhesive with quick grab and rapid set-up for the fast installation of wall base.

#### Features and Benefits

- High-performance acrylic polymer paste
- Extra-high wet strength for bonding heavy rubber base
- Quick grabbing, fast set-up and solvent-free
- Coverage up to 240 linear feet per gallon
- Powered by Microban® for superior mold and mildew protection

#### Approved Flooring Types



Vinyl wall base  
 Rubber wall base  
 Carpet wall base

#### Approved Substrates

Gypsum drywall  
 Brick  
 Concrete Block  
 Wood  
 Properly cured plaster  
 Concrete

For floorings and backings not listed, contact Technical Services at (905) 791-4444 (CA).

### Recommended Trowel and Coverage Rate\*

	<b>3/16" x 5/32" (4.7 mm x 4 mm) V Notch</b>
	Flooring (porous substrate): Wall base 4" (101.6 mm) Coverage: 240 linear ft/per gallon (73.2 m/per 3.78 L)
	<b>1/8" x 1/8" x 1/8" (3 mm x 3mm x 3 mm) SQ Notch</b>
	Flooring (porous substrate): Wall base 4" (101.6 mm) Coverage: 240 linear ft/per gallon (73.2 m/per 3.78 L)

\* NOTE: The trowel notches referenced are those typically recommended for the type of flooring being installed, and are referenced as a guide. Coverage rates will vary depending on trowel type, substrate and installation conditions. Consult flooring manufacturer for their specific trowel recommendations.



SHELF LIFE  
**2 YEARS**



LIFETIME  
**WARRANTY\***

\*Based on installation by an industry certified installer



## 2. TECHNICAL DATA

<b>Product Type:</b>	Acrylic Polymer Paste
<b>Color:</b>	Tan
<b>Odor:</b>	Very mild; odorless when dry
<b>Open Time:</b>	Up to 10 minutes
<b>Working Time:</b>	Up to 30 minutes Setup time will vary slightly with temperature and porosity of substrate
<b>Curing Time:</b>	8-10 hours
<b>Traffic:</b>	Residential: N/A Commercial: 6 hours Rolling Loads: N/A
<b>pH:</b>	8.5-9.0
<b>Shelf Life:</b>	2 years from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning
<b>Storage:</b>	Protect from freezing
<b>VOC:</b>	< 1 g/L

## 3. INSTRUCTIONS

### Limitations

- For interior installations only

### Preparation

Surface must be structurally sound, dry, smooth, flat, free of excess moisture/alkali and all substances (paint, wall coverings, dust, etc.) that might interfere with the performance of the wall base or its installation.

For best results, wrapped or rolled wall base should lay flat for 24 hours before application, and the back of the wall base should be wiped with mineral spirits for maximum adhesion.

### Installation

Materials and area temperature must be between 18-35°C/65-95°F with a maximum RH of 65% for 48 hours before and during installation as well as for 72 hours afterward. Large temperature or humidity increases or decreases can affect the flooring and performance of the installation. Trim any vinyl wall coverings to 1/4" below the top of the wall base with a ROBERTS knife. Apply adhesive uniformly to the wall or to the back of the wall base. Press the wall base firmly in place while the adhesive is still wet (typically within 10 minutes).

Use the ROBERTS® 10-964 Vinyl Seam Roller to press and smooth wall base into the adhesive. Always roll back to the starting point to prevent stretching the adhesive.

### Clean-up

*Fresh adhesive* – warm, soapy water on a clean cloth.

*Dried adhesive* – use mineral spirits sparingly with a clean, white cotton cloth.

## 4. AVAILABILITY



10 L Plastic Pail	7051RB010	075378705130
-------------------	-----------	--------------



## 5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications. **Lifetime Warranty applies only for installations performed by industry certified professional installers.** Visit [robertsconsolidated.com/ca](http://robertsconsolidated.com/ca) or call (866) 435-8665 for full warranty details.

## 6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (905) 791-4444 Canada.



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company.

A2524 12308



**Roberts Company Canada, Ltd.**  
34 Hansen Road, Brampton, ON L6W 3H4  
Customer Service: (866) 435-8665  
Technical Support: (905) 791-4444  
[robertsconsolidated.com/ca](http://robertsconsolidated.com/ca)

