



7250

CORK UNDERLAYMENT PROFESSIONAL-GRADE ADHESIVE



Powered by Microban® for superior mold and mildew protection.

1. DESCRIPTION

ROBERTS® 7250 Cork Underlayment Adhesive is recommended for the installation of acoustical cork underlayment rolls or sheets. It provides a strong initial grab and good tack.

Features and Benefits

- Solvent free, low-VOC formula with strong initial grab and good tack
- Acoustical cork underlayment rolls or sheets
- Moisture control up to 5 lbs. MVER and 80% RH
- Extended working time for optimal positioning
- Coverage up to 190 ft²/gal
- Commercial and residential use
- Powered by Microban® for superior mold and mildew protection

Approved Flooring Types

Acoustical cork underlayment (rolls)

Acoustical cork underlayment (sheets)

Approved Substrates

Concrete

APA-rated plywood

For floorings and backings not listed, contact Technical Services at (706) 277-5294 (U.S.A)

Recommended Trowel and Coverage Rate*

1/8" x 1/8" x 1/16" (3 mm x 3 mm x 1.5 mm) Flat-Top V Notch

Flooring (porous substrate): Cork Underlayment ≤ 3/8"
Coverage: 160-180 ft²/per gallon (14.8-16.7 m²/per 3.78 L)

1/16" x 1/16" x 1/16" (1.5 mm x 1.5 mm x 1.5 mm) SQ Notch

Flooring (porous substrate): Cork Underlayment ≤ 3/8"
Coverage: 170-190 ft²/per gallon (15.8-17.6 m²/per 3.78 L)

* NOTE: The trowel notches referenced are those typically recommended for the type of flooring being installed, and are referenced as a guide. Coverage rates will vary depending on trowel type, substrate and installation conditions. Consult flooring manufacturer for their specific trowel recommendations.

MOISTURE
RESISTANCE

SHELF LIFE
2 YEARS



2. TECHNICAL DATA

Product Type:	Latex
Color:	Tan
Odor:	Very mild
Open Time:	Up to 60 minutes
Working Time:	Up to 90 minutes Setup time will vary slightly with temperature and porosity of substrate
Curing Time:	8-10 hours
Traffic:	Residential: 24 hours Commercial: 24 hours Rolling Loads: N/A
MVER:	5 lbs or less (ASTM F1869) / 80% RH or less (ASTM F2170)
pH:	Must not exceed 10.0
Shelf Life:	2 years from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning
Storage:	Protect from freezing
VOC:	<1 g/L

3. INSTRUCTIONS

Limitations

- Ensure adequate ventilation during flooring installation
- Not recommended for the installation of cork flooring when it is to be the final finished flooring surface

Preparation

Subfloors must be structurally sound, dry, smooth, flat ($\leq 3/16"$ within 10'), level and free of excess moisture/alkali and all substances (oil, wax, grease, paint, oil based sealers, adhesive residue, etc.) that may inhibit the bond of the adhesive or the performance of the flooring or its installation.

All substrate cracks, chips, holes, joints, high spots and irregularities must be adequately repaired. Expansion or other moving joints must not be filled or covered with flooring. Patching compounds must be suitable for the use application, cement based and polymer-modified, and applied according to the manufacturer's instructions.

Installation

Materials and area temperature must be between 65°F-95°F with a maximum relative humidity (RH) of 65% for 72 hours before and during installation as well as for 72 hours afterward. Large temperature or humidity increases or decreases can affect the flooring and performance of the installation. Lift a corner periodically to ensure 100% coverage of adhesive to the flooring backing and the substrate to ensure a void-free bond.

Spread adhesive uniformly. Adhesive ridges should be of sufficient height to achieve full coverage of the substrate and the back of the cork underlayment.

Place underlayment into the adhesive once the adhesive has developed its initial tack. The amount of time in which you have to place the flooring will vary with temperature and humidity.

Clean-up

Fresh adhesive – warm soapy water. Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth. **DO NOT POUR DIRECTLY ONTO FLOORING**

4. AVAILABILITY



4 G Plastic Pail	7250-4	075378725046
1 G Plastic Pail	7250-1	075378725015



5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications. Visit robertsconsolidated.com or call (866) 435-8665 for full warranty details.

6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 U.S.A.



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company.

MO124 12304



Roberts Consolidated Industries, Inc.
300 Cross Plains Blvd, Dalton, GA 30721
Customer Service: (866) 435-8665
Technical Support: (706) 277-5294
robertsconsolidated.com

