



# 8502

## LATEX CARPET SEAM SEALER



Powered by Microban® for superior mold and mildew protection.

### 1. DESCRIPTION

ROBERTS® 8502 Latex Carpet Seam Sealer is a natural latex adhesive recommended for seam sealing carpets, sealing raw edges, binding, strengthening worn backings and applying new backings on area rugs. ROBERTS 8502 may increase slip resistance on mats or rugs and contains a UV tracer for easy detection.

#### Features and Benefits

- Seals and binds carpet edges to prevent raveling
- Contains UV tracers for easy detection
- Use to apply new backings to area rugs
- Provides enhanced slip resistance
- Coverage: 725 linear feet/quart
- Commercial and residential use
- Powered by Microban® for superior mold and mildew protection

#### Approved Carpet Types

Commercial Carpet

Residential Carpet

For floorings and backings not listed, contact Technical Services at (706) 277-5294 (U.S.A) and (905) 791-4444 (CA).

### 2. TECHNICAL DATA

<b>Product Type:</b>	Acrylic Latex
<b>Color:</b>	Off white
<b>Odor:</b>	Very mild, odorless when dry
<b>Open Time:</b>	Up to 10 minutes
<b>Working Time:</b>	Up to 15 minutes Setup time will vary slightly with temperature and porosity of substrate
<b>Curing Time:</b>	12 to 24 hours
<b>Traffic:</b>	Residential: 24 hours Commercial: 24 hours Rolling Loads: N/A
<b>Shelf Life:</b>	1 year from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning
<b>Storage:</b>	Protect from freezing
<b>VOC:</b>	<1 g/L



### 3. INSTRUCTIONS

#### Installation

*Conventional and Double Glue Installations* – Prepare and cut carpet edges according to manufacturer’s recommendation. Apply a 1/8” bead of adhesive to both sides of the carpet along the backing where the face yarns enter the backing (not the cushion) with an applicator bottle. Smooth out any excess adhesive being careful not to get any adhesive on the carpet nap. Allow adhesive to become dry to the touch before joining the seams with a carpet seam tape.

#### Clean-up

Within 10 minutes after seaming carpet use warm, soapy water or mineral spirits sparingly with a clean, white cotton cloth. **DO NOT POUR CLEANER DIRECTLY ONTO FLOORING. USING TOO MUCH CLEANER CAN CAUSE PERMANENT DAMAGE AND TEMPORARY SWELLING OF THE CARPET.** Remove any traces of adhesive on unwanted areas of the carpet. Ensure there is no excess adhesive left on the face of the yarn that can eventually attract dirt.

### 4. AVAILABILITY



**USA**

1 Q Plastic Bottle	8502-0	075378850205
--------------------	--------	--------------



**Canada**

946 mL Plastic Bottle	8502RB001	075378850298
-----------------------	-----------	--------------



### 5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications. Visit [robertsconsolidated.com](http://robertsconsolidated.com), [robertsconsolidated.com/ca](http://robertsconsolidated.com/ca) or call (866) 435-8665 for full warranty details.

### 6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 U.S.A. / (905) 791-4444 Canada.



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company.

A2324 12303



**Roberts Consolidated Industries, Inc.**  
 300 Cross Plains Blvd, Dalton, GA 30721  
 Customer Service: (866) 435-8665  
 Technical Support: (706) 277-5294  
[robertsconsolidated.com](http://robertsconsolidated.com)



**Roberts Company Canada, Ltd.**  
 34 Hansen Road, Brampton, ON L6W 3H4  
 Customer Service: (866) 435-8665  
 Technical Support: (905) 791-4444  
[robertsconsolidated.com/ca](http://robertsconsolidated.com/ca)

