



# 8600

## NOSE BOND® STAIR NOSE ADHESIVE



Powered by Microban® for superior mold and mildew protection.

### 1. DESCRIPTION

ROBERTS® 8600 NOSE BOND® is specifically designed for interior stair nose installations on properly prepared wood subfloors. Use with wood, laminate, and rigid PVC stair nose used with vinyl floors.

#### Features and Benefits

- Ideal for wood, laminate and rigid PVC stair nosing
- Can also be used for wood moldings, wood trim installs and repairs
- Easy clean up
- Commercial and residential use
- Coverage up to 30 lineal feet / per 10 oz cartridge
- Powered by Microban® for superior mold and mildew protection

#### Approved Flooring Types

Stair Nose - Wood, laminate and rigid PVC stair nose used with vinyl floors

*For floorings and backings not listed, contact Technical Services at (706) 277-5294 (U.S.A) and (905) 791-4444 (CA).*

### 2. TECHNICAL DATA

<b>Product Type:</b>	Advanced Acrylic Adhesive
<b>Color:</b>	Beige
<b>Odor:</b>	Very mild, non-offensive
<b>Open Time:</b>	Up to 20 minutes
<b>Working Time:</b>	Up to 30 minutes Setup time will vary slightly with temperature and porosity of substrate
<b>Curing Time:</b>	8-10 hours
<b>Traffic:</b>	Residential: 24 hours Commercial: 24 hours Rolling Loads: N/A
<b>Shelf Life:</b>	2 years from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning
<b>Storage:</b>	Protect from freezing
<b>VOC:</b>	2 g/L



SHELF LIFE  
**2 YEARS**

### 3. INSTRUCTIONS

#### Limitations

- For interior installations only
- Not recommended over non-porous materials or painted surfaces
- Concrete and plaster must be properly seasoned and dry prior to installation

#### Preparation

Surface must be clean, dry and free of contaminants that might interfere with the bond or the installation.

#### Installation

Apply a serpentine pattern bead to the underside of the stair nose, and a bead along the inside front edge. Press into place. Apply mechanical fasteners (as needed) per manufacturer's guidelines.

#### Clean-up

*Fresh adhesive* – warm, soapy water on a clean cloth.

*Dried adhesive* – use mineral spirits sparingly with a clean, white cotton cloth.

### 4. AVAILABILITY

USA		
10 Oz Tube	8600-10C	075378716013



Canada		
295 mL Tube	8600-10C	075378716013



### 5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications. Visit [robertsconsolidated.com](http://robertsconsolidated.com), [robertsconsolidated.com/ca](http://robertsconsolidated.com/ca) or call (866) 435-8665 for full warranty details.

### 6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 U.S.A. / (905) 791-4444 Canada.



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company.

H1924 12281



**Roberts Consolidated Industries, Inc.**  
300 Cross Plains Blvd, Dalton, GA 30721  
Customer Service: (866) 435-8665  
Technical Support: (706) 277-5294  
[robertsconsolidated.com](http://robertsconsolidated.com)



**Roberts Company Canada, Ltd.**  
34 Hansen Road, Brampton, ON L6W 3H4  
Customer Service: (866) 435-8665  
Technical Support: (905) 791-4444  
[robertsconsolidated.com/ca](http://robertsconsolidated.com/ca)

