



# 7500

## VINYL SEAM SEALER FOR SHEET FLOORING



Powered by Microban® for superior mold and mildew protection.

### 1. DESCRIPTION

**ROBERTS® 7500 VINYL SEAM SEALER** is a strong adhesive designed to seal seams in sheet flooring. With its easy application and clean-up, this durable bonding seam sealer is used with fiberglass-backed, felt-backed, heterogeneous and linoleum sheets goods

#### Features and Benefits

- Simple one-part application with easy clean up
- Creates strong, durable bond that can be walked on within two hours
- Fiberglass-back, felt-back, heterogeneous and linoleum sheet goods
- Coverage up to 144 linear feet / per 8 oz
- Powered by Microban® for superior mold and mildew protection

#### Approved Flooring Types

Fiberglass-backed sheet vinyl

Felt-backed sheet vinyl

Linoleum

*For floorings and backings not listed, contact Technical Services at (706) 277-5294 (U.S.A) and (905) 791-4444 (CA).*

### 2. TECHNICAL DATA

**Product Type:** Polymer-Synthetic Resin

**Color:** White

**Odor:** Very mild, non-offensive

**Open Time:** 5-10 minutes

**Working Time:** Up to 15 minutes

*Setup time will vary slightly with temperature and porosity of substrate*

**Curing Time:** 2-6 hours. Do not roll heavy furniture or appliance over the newly created seam for 24 hours.

**Traffic:** Residential: 24 hours  
Commercial: 24 hours  
Rolling Loads: N/A

**pH:** 5.5

**Shelf Life:** 1 year from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning

**Storage:** Protect from freezing

**VOC:** <1 g/mL



### 3. INSTRUCTIONS

#### Limitations

- For interior installations only
- Not for use in healthcare installs where an aseptic environment is necessary
- Not for use on degraded / ripped / rolled seams, or for use as gap filler

#### Installation

Overlap and double cut the seam using a scrap piece of flooring, under the cut location. Roll the flooring back. Finish gluing the seam area. Fold one side into the adhesive or on tape. Apply a 1/8" bead along the seam edge and tuck edge into place. Wipe seam with a dry, clean white cloth. Roll seam with a hand roller. Repeat as needed. Clean the seam again with the same process.

#### Clean-up

*Fresh adhesive* – warm, soapy water on a clean cloth.

*Dried adhesive* – use mineral spirits sparingly with a clean, white cotton cloth. DO NOT POUR DIRECTLY ONTO FLOORING.

### 4. AVAILABILITY



USA\*\*

8 Oz Plastic Bottle	7500-8	075378750086
---------------------	--------	--------------



Canada

236 mL Plastic Bottle	7500RB250	075378750086
-----------------------	-----------	--------------



### 5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications. Visit [robertsconsolidated.com](http://robertsconsolidated.com), [robertsconsolidated.com/ca](http://robertsconsolidated.com/ca) or call (866) 435-8665 for full warranty details.

### 6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 U.S.A. / (905) 791-4444 Canada.



ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company  
 \*\* Note: Only product manufactured in the USA is FloorScore Certified

H0525 12281



**Roberts Consolidated Industries, Inc.**  
 300 Cross Plains Blvd, Dalton, GA 30721  
 Customer Service: (866) 435-8665  
 Technical Support: (706) 277-5294  
[robertsconsolidated.com](http://robertsconsolidated.com)



**Roberts Company Canada, Ltd.**  
 34 Hansen Road, Brampton, ON L6W 3H4  
 Customer Service: (866) 435-8665  
 Technical Support: (905) 791-4444  
[robertsconsolidated.com/ca](http://robertsconsolidated.com/ca)

